



| 规格 | |
|--------|-----------|
| 压力角 | 20° |
| 旋向 | 右 |
| 螺旋角 | 19°31'42" |
| 材料 | C45 |
| 热处理 | 调质 |
| 齿部加工方式 | 铣削 |
| 精度等级 | 8e27 |
| 端部连接方式 | 可拼接安装 |

| 齿条号 | 模数 | L | L1 | B | H | h | 齿数 | l | l1 | l2 | l3 | b1 | h1 | d1 | d2 | d3 | f | 孔数 | 重量 (kg) |
|------------|----|---------|------|----|----|----|-----|--------|------|-----|------|----|----|----|----|------|---|----|---------|
| SR2-050RQB | 2 | 500.00 | 8.9 | 25 | 24 | 22 | 75 | 436.6 | 31.7 | 125 | 62.5 | 7 | 8 | 7 | 11 | 5.7 | 2 | 4 | 2.10 |
| SR2-100RQB | 2 | 1000.00 | 8.9 | 25 | 24 | 22 | 150 | 936.6 | 31.7 | 125 | 62.5 | 7 | 8 | 7 | 11 | 5.7 | 2 | 8 | 4.30 |
| SR2-200RQB | 2 | 2000.00 | 8.9 | 25 | 24 | 22 | 300 | 1936.6 | 31.7 | 125 | 62.5 | 7 | 8 | 7 | 11 | 5.7 | 2 | 16 | 8.60 |
| SR3-050RQB | 3 | 500.00 | 10.6 | 30 | 29 | 26 | 50 | 430.0 | 35.0 | 125 | 62.5 | 9 | 9 | 10 | 15 | 7.7 | 2 | 4 | 3.00 |
| SR3-100RQB | 3 | 1000.00 | 10.6 | 30 | 29 | 26 | 100 | 930.0 | 35.0 | 125 | 62.5 | 9 | 9 | 10 | 15 | 7.7 | 2 | 8 | 6.10 |
| SR3-200RQB | 3 | 2000.00 | 10.6 | 30 | 29 | 26 | 200 | 1930.0 | 35.0 | 125 | 62.5 | 9 | 9 | 10 | 15 | 7.7 | 2 | 16 | 12.20 |
| SR4-050RQB | 4 | 506.67 | 14.2 | 40 | 39 | 35 | 38 | 433.0 | 33.3 | 125 | 62.5 | 9 | 12 | 10 | 15 | 7.7 | 2 | 4 | 5.50 |
| SR4-100RQB | 4 | 1000.00 | 14.2 | 40 | 39 | 35 | 75 | 933.4 | 33.3 | 125 | 62.5 | 9 | 12 | 10 | 15 | 7.7 | 2 | 8 | 10.90 |
| SR4-200RQB | 4 | 2000.00 | 14.2 | 40 | 39 | 35 | 150 | 1933.4 | 33.3 | 125 | 62.5 | 9 | 12 | 10 | 15 | 7.7 | 2 | 16 | 21.80 |
| SR5-050RQB | 5 | 500.00 | 17.4 | 50 | 39 | 34 | 30 | 425.0 | 37.5 | 125 | 62.5 | 13 | 12 | 14 | 20 | 11.7 | 3 | 8 | 6.50 |
| SR5-100RQB | 5 | 1000.00 | 17.4 | 50 | 39 | 34 | 60 | 925.0 | 37.5 | 125 | 62.5 | 13 | 12 | 14 | 20 | 11.7 | 3 | 8 | 13.00 |
| SR5-200RQB | 5 | 2000.00 | 17.4 | 50 | 39 | 34 | 120 | 1925.0 | 37.5 | 125 | 62.5 | 13 | 12 | 14 | 20 | 11.7 | 3 | 16 | 26.00 |

注: 1 所有尺寸均为毫米。
2 尺寸和其它技术数据可能会有变化, 核准数据承索即供。