



| 规格 | |
|--------|--------|
| 压力角 | 20° |
| 材料 | C45 |
| 热处理 | 齿面高频淬火 |
| 齿部加工方式 | 磨削 |
| 精度等级 | 6h25 |
| 端部连接方式 | 可拼接安装 |

| 齿条号 | 模数 | L | B | H | h | 齿数 | f | 重量 (kg) |
|------------|----|---------|----|----|----|-----|---|---------|
| SR2-100GE | 2 | 1005.30 | 24 | 24 | 22 | 160 | 2 | 4.20 |
| SR2-200GE | 2 | 2010.62 | 24 | 24 | 22 | 320 | 2 | 8.40 |
| SR3-100GE | 3 | 1017.90 | 29 | 29 | 26 | 108 | 2 | 6.00 |
| SR3-200GE | 3 | 2035.75 | 29 | 29 | 26 | 216 | 2 | 12.00 |
| SR4-100GE | 4 | 1005.30 | 39 | 39 | 35 | 80 | 3 | 10.50 |
| SR4-200GE | 4 | 2010.62 | 39 | 39 | 35 | 160 | 3 | 21.00 |
| SR5-020GE | 5 | 251.32 | 49 | 39 | 34 | | | 3.35 |
| SR5-050GE | 5 | 502.60 | 49 | 39 | 34 | 32 | 3 | 6.70 |
| SR5-100GE | 5 | 1005.30 | 49 | 39 | 34 | 64 | 3 | 13.40 |
| SR5-150GE | 5 | 1507.96 | 49 | 39 | 34 | 96 | 3 | 20.10 |
| SR5-200GE | 5 | 2010.62 | 49 | 39 | 34 | 128 | 3 | 26.80 |
| SR6-020GE | 6 | 245.04 | 59 | 49 | 43 | | | 5.05 |
| SR6-050GE | 6 | 508.90 | 59 | 49 | 43 | 27 | 3 | 10.10 |
| SR6-100GE | 6 | 1017.80 | 59 | 49 | 43 | 54 | 3 | 20.20 |
| SR6-150GE | 6 | 1526.81 | 59 | 49 | 43 | 81 | 3 | 30.30 |
| SR6-200GE | 6 | 2035.75 | 59 | 49 | 43 | 108 | 3 | 40.40 |
| SR8-020GE | 8 | 251.32 | 79 | 79 | 71 | | | 0.58 |
| SR8-050GE | 8 | 502.65 | 79 | 79 | 71 | 20 | 3 | 22.38 |
| SR8-100GE | 8 | 1005.30 | 79 | 79 | 71 | 40 | 3 | 44.76 |
| SR8-200GE | 8 | 2010.61 | 79 | 79 | 71 | 80 | 3 | 89.50 |
| SR10-020GE | 10 | 219.91 | 99 | 99 | 89 | | | 14.20 |
| SR10-100GE | 10 | 1005.30 | 99 | 99 | 89 | 32 | 3 | 68.72 |

注: 1 所有尺寸均为毫米。
2 尺寸和其它技术数据可能会有变化, 核准数据承索即供。