



规格	
压力角	20°
材料	C45
热处理	调质
齿部加工方式	铣削
精度等级	8e27
端部连接方式	可拼接安装

齿条号	模数	L	B	H	h	齿数	l	l1	l2	l3	b1	h1	d1	d2	d3	f	孔数	重量 (kg)
SR2-050QB	2	502.65	25	24	22	80	440.1	31.3	125.66	62.83	7	8	7	11	5.7	2	4	2.20
SR2-100QB	2	1005.31	25	24	22	160	942.7	31.3	125.66	62.83	7	8	7	11	5.7	2	8	4.30
SR2-200QB	2	2010.62	25	24	22	320	1948.0	31.3	125.66	62.83	7	8	7	11	5.7	2	16	8.60
SR3-050QB	3	508.94	30	29	26	54	440.1	34.4	127.23	63.62	9	9	10	15	7.7	2	4	3.10
SR3-100QB	3	1017.88	30	29	26	108	949.1	34.4	127.23	63.62	9	9	10	15	7.7	2	8	6.20
SR3-200QB	3	2035.75	30	29	26	216	1967.0	34.4	127.23	63.62	9	9	10	15	7.7	2	16	12.40
SR4-050QB	4	502.65	40	39	35	40	427.7	37.5	125.66	62.83	9	12	10	15	7.7	2	4	5.50
SR4-100QB	4	1005.31	40	39	35	80	930.3	37.5	125.66	62.83	9	12	10	15	7.7	3	8	11.00
SR4-200QB	4	2010.62	40	39	35	160	1935.6	37.5	125.66	62.83	9	12	10	15	7.7	3	16	22.00
SR5-050QB	5	502.65	49	39	34	32	442.3	30.2	125.66	62.83	13	12	14	20	11.7	3	4	6.80
SR5-100QB	5	1005.31	49	39	34	64	945.0	30.2	125.66	62.83	13	12	14	20	11.7	3	8	13.60
SR5-200QB	5	2010.62	49	39	34	128	1950.4	30.2	125.66	62.83	13	12	14	20	11.7	3	16	27.20

注: 1 所有尺寸均为毫米。
2 尺寸和其它技术数据可能会有变化, 核准数据承索即供。