



规格	
压力角	20°
材料	C45
热处理	齿面高频淬火
齿部加工方式	铣削
精度等级	10e27
端部连接方式	可拼接安装

齿条号	模数	L	B	H	h	齿数	l	l1	l2	l3	b1	h1	d1	d2	d3	f	孔数	重量 (kg)
SR2-050HB	2	502.65	24	24	22	80	440.1	31.3	125.66	62.83	7	8	7	11	5.7	2	4	2.10
SR2-100HB	2	1005.31	24	24	22	160	942.7	31.3	125.66	62.83	7	8	7	11	5.7	2	8	4.20
SR2-200HB	2	2010.62	24	24	22	320	1948.0	31.3	125.66	62.83	7	8	7	11	5.7	2	16	8.40
SR3-050HB	3	508.94	29	29	26	54	440.1	34.4	127.23	63.62	9	9	10	15	7.7	2	4	3.00
SR3-100HB	3	1017.88	29	29	26	108	949.1	34.4	127.23	63.62	9	9	10	15	7.7	2	8	6.00
SR3-200HB	3	2035.75	29	29	26	216	1967.0	34.4	127.23	63.62	9	9	10	15	7.7	2	16	12.00
SR4-050HB	4	502.65	39	39	35	40	427.7	37.5	125.66	62.83	9	12	10	15	7.7	3	4	5.30
SR4-100HB	4	1005.31	39	39	35	80	930.3	37.5	125.66	62.83	9	12	10	15	7.7	3	8	10.20
SR4-200HB	4	2010.62	39	39	35	160	1935.6	37.5	125.66	62.83	9	12	10	15	7.7	3	16	20.50
SR5-050HB	5	502.65	49	49	34	32	442.3	30.2	125.66	62.83	13	12	14	20	11.7	3	4	6.90
SR5-100HB	5	1005.31	49	49	34	64	945.0	30.2	125.66	62.83	13	12	14	20	11.7	3	8	13.80
SR5-200HB	5	2010.62	49	49	34	128	1950.3	30.2	125.66	62.83	13	12	14	20	11.7	3	16	27.50
SR6-050HB	6	508.94	59	49	43	27	446.1	31.4	127.23	63.62	17	16	18	26	15.7	3	4	10.50
SR6-100HB	6	1017.88	59	49	43	54	955.0	31.4	127.23	63.62	17	16	18	26	15.7	3	8	21.00
SR6-200HB	6	2035.75	59	49	43	108	1972.9	31.4	127.23	63.62	17	16	18	26	15.7	3	16	42.00

注: 1 所有尺寸均为毫米。
2 尺寸和其它技术数据可能会有变化, 核准数据承索即供。