



规格	
压力角	20°
材料	C45
热处理	-
齿部加工方式	铣削
精度等级	9e27
端部连接方式	可拼接安装

齿条号	模数	L	D _{h11}	b	H	h	齿数	重量 (kg)
SRR1-020E	1	251.3	15	7.5	15	14.0	80	0.34
SRR1-050E	1	499.5	15	7.5	15	14.0	159	0.65
SRR1-100E	1	999.0	15	7.5	15	14.0	318	1.35
SRR1.5-020E	1.5	249.8	17	9.6	17	15.5	53	0.42
SRR1.5-050E	1.5	499.5	17	9.6	17	15.5	106	0.84
SRR1.5-100E	1.5	999.0	17	9.6	17	15.5	212	1.70
SRR2-020E	2	251.3	20	12.0	20	18.0	40	0.55
SRR2-050E	2	502.7	20	12.0	20	18.0	80	1.10
SRR2-100E	2	999.0	20	12.0	20	18.0	159	2.20
SRR2.5-020E	2.5	251.3	25	15.0	25	22.5	32	0.90
SRR2.5-050E	2.5	502.7	25	15.0	25	22.5	64	1.80
SRR2.5-100E	2.5	997.5	25	15.0	25	22.5	127	3.60
SRR3-020E	3	254.5	30	18.0	30	27.0	27	1.30
SRR3-050E	3	499.5	30	18.0	30	27.0	53	2.50
SRR3-100E	3	999.0	30	18.0	30	27.0	106	5.10
SRR4-020E	4	251.3	40	24.0	40	36.0	20	2.30
SRR4-050E	4	502.6	40	24.0	40	36.0	40	4.50
SRR4-100E	4	1005.3	40	24.0	40	36.0	80	9.10
SRR5-020E	5	251.3	50	30.0	50	45.0	16	3.80
SRR5-050E	5	502.6	50	30.0	50	45.0	32	7.10
SRR5-100E	5	1005.3	50	30.0	50	45.0	64	14.30

注: 1 所有尺寸均为毫米。

2 尺寸和其它技术数据可能会有变化, 核准数据承索即供。