



规格	
压力角	20°
旋向	右
螺旋角	19°31'42"
材料	C45
热处理	-
齿部加工方式	铣削
精度等级	9e27
端部连接方式	可拼接安装

齿条号	模数	L	L1	B	H	h	齿数	l	l1	l2	l3	b1	h1	d1	d2	d3	f	孔数	重量 (kg)
SR2-050RB	2	500.00	9.2	26	24	22	75	436.6	31.7	125	62.5	7	8	7	11	5.7	-	4	2.20
SR2-100RB	2	1000.00	9.2	26	24	22	150	936.6	31.7	125	62.5	7	8	7	11	5.7	-	8	4.40
SR2-200RB	2	2000.00	9.2	26	24	22	300	1936.6	31.7	125	62.5	7	8	7	11	5.7	-	16	8.80
SR3-050RB	3	500.00	11.0	31	29	26	50	430.0	35.0	125	62.5	9	9	10	15	7.7	-	4	3.10
SR3-100RB	3	1000.00	11.0	31	29	26	100	930.0	35.0	125	62.5	9	9	10	15	7.7	-	8	6.20
SR3-200RB	3	2000.00	11.0	31	29	26	200	1930.0	35.0	125	62.5	9	9	10	15	7.7	-	16	12.50
SR4-050RB	4	506.67	14.5	41	39	35	38	433.0	33.3	125	62.5	9	12	10	15	7.7	-	4	5.60
SR4-100RB	4	1000.00	14.5	41	39	35	75	933.4	33.3	125	62.5	9	12	10	15	7.7	-	8	11.10
SR4-200RB	4	2000.00	14.5	41	39	35	150	1933.4	33.3	125	62.5	9	12	10	15	7.7	-	16	22.20
SR5-100RB	5	1000.00	17.7	50	39	34	60	925.0	37.5	125	62.5	13	12	14	20	11.7	-	8	13.26
SR5-200RB	5	2000.00	17.7	50	39	34	120	1925.0	37.5	125	62.5	13	12	14	20	11.7	-	16	26.52
SR6-100RB	6	1000.00	21.3	60	49	43	50	925.0	37.5	125	62.5	17	16	18	26	15.7	-	8	20.12
SR6-200RB	6	2000.00	21.3	60	49	43	100	1925.0	37.5	125	62.5	17	16	18	26	15.7	-	16	40.24
SR8-100RB	8	960.00	28.7	81	79	71	36	720.0	120.0	120	60.0	21	25	25	33	19.7	-	8	44.85
SR8-200RB	8	1920.00	28.7	81	79	71	72	1680.0	120.0	120	60.0	21	25	22	33	19.7	-	16	89.71
SR10-100RB	10	1000.00	35.5	100	99	89	30	750.0	125.0	125	62.5	32	32	33	48	19.7	-	8	69.80

注: 1 所有尺寸均为毫米。
2 尺寸和其它技术数据可能会有变化, 核准数据承索即供。