



规格	
压力角	20°
旋向	右
螺旋角	19°31'42"
材料	C45
热处理	齿面高频淬火
齿部加工方式	铣削
精度等级	10e27
端部连接方式	可拼接安装

齿条号	模数	L	L1	B	H	h	齿数	l	l1	l2	l3	b1	h1	d1	d2	d3	f	孔数	重量 (kg)
SR2-050RHB	2	500.00	8.5	24	24	22	75	436.6	31.7	125	62.5	7	8	7	11	5.7	2	4	2.10
SR2-100RHB	2	1000.00	8.5	24	24	22	150	936.6	31.7	125	62.5	7	8	7	11	5.7	2	8	4.20
SR3-050RHB	3	500.00	10.3	29	29	26	50	430.0	35.0	125	62.5	9	9	10	15	7.7	2	4	3.00
SR3-100RHB	3	1000.00	10.3	29	29	26	100	930.0	35.0	125	62.5	9	9	10	15	7.7	2	8	6.00
SR4-050RHB	4	506.67	13.8	39	39	35	38	433.0	33.3	125	62.5	9	12	10	15	7.7	3	4	5.30
SR4-100RHB	4	1000.00	13.8	39	39	35	75	933.4	33.3	125	62.5	9	12	10	15	7.7	3	8	10.50
SR5-050RHB	5	500.00	17.4	49	39	34	30	425.0	37.5	125	62.5	13	12	14	20	11.7	3	4	6.50
SR5-100RHB	5	1000.00	17.4	49	39	34	60	925.0	37.5	125	62.5	13	12	14	20	11.7	3	8	13.00
SR6-050RHB	6	500.00	20.9	59	49	43	25	425.0	37.5	125	62.5	17	16	18	26	15.7	3	4	9.90
SR6-100RHB	6	1000.00	20.9	59	49	43	50	925.0	37.5	125	62.5	17	16	18	26	15.7	3	8	19.80

注: 1 所有尺寸均为毫米。
2 尺寸和其它技术数据可能会有变化, 核准数据承索即供。