



规格	
压力角	20°
材料	C45
热处理	-
齿部加工方式	铣削

齿条号	径节	齿距	L	B	H	h	重量 (Lbs)
SRDP3-24	3	1.047	24	3.000	1.500	1.167	24.00
SRDP3-48	3	1.047	48	3.000	1.500	1.167	48.00
SRDP3-72	3	1.047	72	3.000	1.500	1.167	72.00
SRDP4-24	4	0.785	24	2.000	1.500	1.250	17.40
SRDP4-48	4	0.785	48	2.000	1.500	1.250	34.80
SRDP4-72	4	0.785	72	2.000	1.500	1.250	52.20
SRDP5-24	5	0.628	24	1.750	1.250	1.050	12.80
SRDP5-48	5	0.628	48	1.750	1.250	1.050	25.60
SRDP5-72	5	0.628	72	1.750	1.250	1.050	38.40
SRDP6-24	6	0.524	24	1.500	1.250	1.333	13.80
SRDP6-48	6	0.524	48	1.500	1.250	1.333	27.60
SRDP6-72	6	0.524	72	1.500	1.250	1.333	41.40
SRDP8-24	8	0.393	24	1.250	1.250	1.125	9.80
SRDP8-48	8	0.393	48	1.250	1.250	1.125	19.60
SRDP8-72	8	0.393	72	1.250	1.250	1.125	29.40
SRDP10-24	10	0.314	24	1.000	1.000	0.900	6.00
SRDP10-48	10	0.314	48	1.000	1.000	0.900	12.00
SRDP10-72	10	0.314	72	1.000	1.000	0.900	18.00
SRDP12-24	12	0.262	24	0.750	0.750	0.667	3.40
SRDP12-48	12	0.262	48	0.750	0.750	0.667	6.80
SRDP12-72	12	0.262	72	0.750	0.750	0.667	10.20
SRDP16-24	16	0.196	24	0.500	0.500	0.438	1.52
SRDP16-48	16	0.196	48	0.500	0.500	0.438	3.04
SRDP16-72	16	0.196	72	0.500	0.500	0.438	4.56
SRDP20-24	20	0.157	24	0.375	0.375	0.325	0.84
SRDP20-48	20	0.157	48	0.375	0.375	0.325	1.68
SRDP20-72	20	0.157	72	0.375	0.375	0.325	2.52

注: 1 所有尺寸均为英寸。
2 尺寸和其它技术数据可能会有变化, 核准数据承索即供。